



### → Dimensions

<b>A</b> (mm)	min 100 max 1000
<b>Hc</b> (mm)	
<b>Hs</b> (mm)	
<b>l</b> (mm)	
<b>α</b> (degrees)	
<b>Capacity</b> (kg)	
<b>Output</b> (pc/min)	

### Material to be conveyed

Specify presence of lubricant, coolant or other fluid, if present.

### → Standard features

#### DRIVE UNIT

- Position: LH side
- Speed: 6 m/min fixed
- Voltage: 400 V / 50 Hz
- With ON/OFF switch

#### BELT

- Smooth green PU covering (ref. Pantone 320)
- Vulcanized belt joint
- Heat-welded slats  
h 30 mm pitch = A
- Operating temperature:  
-10 °C to +90 °C

### → Notes

### → Options

#### BELT

High grip, green PVC (ref. Pantone 320)

High grip PVC + slats h  mm pitch

Smooth PU + slats h 50 mm pitch

3-layers, high-resistance belt + slats  mm pitch

#### CONTROL PANEL

**INVERTER:** adjustable speed from  to  m/min

**PAUSE/WORK:** timed run and stop

**PULSE:** timed run activated by voltage-free external signal

**FEEDER:** run and stop controlled by voltage-free external signal

#### DRIVE UNIT

Mounted on opposite side: RH side

#### SPECIAL OPTIONS

Side protection strips

Special sidewalls  
h

Plate Metal Detector  
installed under belt

